

## Océ View-Through Backlit Film-Océ FBUC07VT and Océ FB05VT

*Film for shiny full color backlits and extra protected prints*

**Océ-Imaging  
Supplies**

Product Info

**View-  
Through  
Backlit  
Film**

*Display Graphics*  
Version 2  
8-25-00



<b>Product Description</b>	Polyester film coated with translucent and inkjet receptive coating layers on one side and a matte semi-translucent layer for good backlit viewing on the reverse side.		
<b>Physical Properties</b>	Caliper	7 mil (FBUC07VT)	5 mil (FB05VT)
	Opacity	65%	63%
<b>Features</b>	Special topcoat with a matte diffusion layer. Easy handling; resistant to wrinkling, good feeding properties. Very good dimensional stability. Tear resistant and durable. Good wind and unwind performance. Wide gamut and rich colors in backlit application, with both lights on and lights off.		

Available sizes & Item Numbers	FBUC07VT			FB05VT		
	Width	x	Length	Width	x	Length
	24"	x	90'	24"	x	100'
			FBUC07VT01			FB05VT0001
	36"	x	90'	36"	x	100'
			FBUC07VT03			FB05VT0002
	42"	x	90'	42"	x	100'
			FBUC07VT04			FB05VT0003
	50"	x	90'	50"	x	100'
			FBUC07VT05			FB05VT0004
	54"	x	90'	54"	x	100'
			FBUC07VT06			FB05VT0005
	60"	x	90'	60"	x	100'
			FBUC07VT07			FB05VT0006

<b>Storage conditions &amp; Shelf Life</b>	Temperature 68-77°F. (20-25°C°). Relative Humidity 30-70%. Please repack opened rolls when not in use. Two years at conditions noted above. Allow material to adapt to room conditions 24 hours before printing.
--	--

<b>Environment, Health &amp; Safety</b>	No Material Safety Data Sheet required. Waste not suitable for recycling.
---	--

<b>Main applications</b>	High quality light box signage. Displays for Trade Shows and Exhibitions. Window and store fixture displays. Vending, arcade and game machine displays.
--------------------------	--

<b>Lamination Tips</b>	Suited for pressure sensitive and heat activated lamination. For heat activated lamination, allow the print to dry thoroughly. Lamination is essential for water fastness. Lamination, in general, will not improve UV resistance significantly. One-sided lamination may cause curl.
------------------------	---

<b>Printer Compatibility</b>	For printer compatibility tables and to find out what printers this product works best with, go to <a href="http://www.oceusa.com">www.oceusa.com</a> and download the latest version of Océ compatibility chart.
------------------------------	---

# Océ View-Through Backlit Film-Océ FBUC07VT and FB05VT

---

<b>Outdoor Suitability</b>	This material was not developed for outdoor use. For outdoor applications, Océ outdoor media and inks are recommended.
<b>Processing Tips</b>	Outside of roll is side to be printed. Use of gloves when handling is recommended. Print in a dust and dirt free environment (60-85°F, 30-70% RH). Check and clean cartridge prior to printing. Recommended ink laydown not to exceed 240%. Use process black as opposed to composite black for optimum results. For HP 2x00 and 3x00 printers use "test media" to determine best setting for printing.
<b>Application Tips</b>	This information is presented as a general guide only and is not a performance guarantee. Test first! This product will provide acceptable print image quality and dry times when used with the recommended OEM ink sets as noted in the Printer Compatibility chart on Océ website listed below. The user should independently determine, prior to use, the suitability of the material for the specific purpose. Recommended minimum surface application temperature for these products is 40°F.
<b>User Tips</b>	In order to prevent problems with cartridges, preventive maintenance by the customer on a daily basis is essential. Prior to starting your print job make a prime test plot. If not all nozzles are open, redo this test or make a "color test" print. Keep cartridges and their environment as clean as possible. Clean the service station assembly with water on a regular basis (preferably each day). Keep electrical contacts, flex cables and carrier clean from ink. Switch on the Auto Wipe mode. Be sure that the ink system is "closed"; there should be no air in the ink tubing system. Refill cartridges correctly (refer to the printer manual). Store cartridges correctly (use "print head garage").
<b>Color Profiles</b> <b>Océ Display</b> <b>Graphics Printers</b>	Color profiles are ink, media and machine specific. Color profiles for Océ printers will improve image quality. Océ equipment color profiles are available from the Océ web site: <a href="http://www.oceusa.com">http://www.oceusa.com</a> . For HP 2x00 and 3x00 printers use "test media" to determine best setting for printing. All other printer profiles are available from Océ website <a href="http://www.oceusa.com/resourcecenter">http://www.oceusa.com/resourcecenter</a>

---

## Performance on major Display Graphics Media

For performance of these inks on the various Océ Media please refer to the Product Information Sheets of the media.



---

### Océ-USA, Inc. Océ-Imaging Supplies

1800 Bruning Drive West  
Itasca, IL 60143-1093  
1-800-323-4827  
[www.oceusa.com](http://www.oceusa.com)

---

### Océ-Imaging Supplies

Product Info

### View- Through Backlit Film

*Display Graphics*  
Version 2  
8-25-00