

New and Improved - Océ PhotoPerfect Plus - GIPPLS7 Glossy and SIPPLS7 Satin Photopaper

Photopaper for digitally produced presentations with color accents that pop

Product Description 7 mil, 50lbs., (190g/m²) bright white photopaper. High opacity resin coated base with inkjet receptive layer on one side to control dot gain and facilitate lamination and backcoat for balance and mounting. Inkjet coating compatible with many wide format and piezo inkjet printers.

| Physical Properties | GIPPL7 | SIPPL7 |
|---------------------|----------|----------|
| Weight | 50lb. | 50lb. |
| Caliper | 7.6 mil | 7.3 mil |
| Opacity | min. 95% | min. 95% |
| Whiteness | 110 | 110 |
| Brightness | 92 | 93 |
| Gloss (60°) | 80 nom. | 45 nom. |

Features True dye and pigment ink compatibility.
Highest quality of photobase media.
Bright white appearance.
Excellent color gamut.
Good handling and feeding properties.
Ability to handle heavy inks loads.
Fast drying properties.
No soak through or cockling.
Excellent laminating and mounting.

| Available sizes & Item Numbers | Width | x | Length | GIPPLS7 | SIPPLS7 |
|--------------------------------|-------|---|--------|------------|------------|
| | 24" | x | 100' | GIPPLS7001 | SIPPLS7001 |
| | 36" | x | 100' | GIPPLS7002 | SIPPLS7002 |
| | 42" | x | 100' | GIPPLS7003 | SIPPLS7003 |
| | 50" | x | 100' | GIPPLS7004 | SIPPLS7004 |
| | 54" | x | 100' | GIPPLS7005 | SIPPLS7005 |
| | 60" | x | 100' | GIPPLS7006 | SIPPLS7006 |
| | 24" | x | 5' | GIPPLS7007 | SIPPLS7007 |

Storage conditions Temperature 50-86°F. (25-30°C).
Relative Humidity 20-70%.
Please repack opened rolls when not in use.

Operating conditions Temperature 18-30°C (60-85°F).
Relative Humidity 20-70%. (non-condensing)

Shelf Life Two years at conditions noted above.
Allow material to adapt to room conditions 24 hours before printing.

Environment, Health & Safety No Material Safety Data Sheet required.
Paper waste suitable for recycling.

Océ Imaging Supplies

Product Info

Photo Perfect Plus

Display Graphics

Version 2

9-23-04



Océ PhotoPerfect Plus - GIPPLS7 & SIPPLS7

| | |
|---|--|
| Main applications | Indoor signage (posters, point-of-purchase, displays). Presentations/Exhibitions. Retail signage. Any application requiring photorealistic images and photographic paper feel. |
| Printer Compatibility | For printer compatibility tables and to find out what printers this product works best with, go to www.oceusa.com and download the latest version Océ compatibility chart. |
| Lamination Tips | Suited for both cold and heat activated (max 185-190°F) lamination. One-sided lamination may cause curl. Lamination is restricted to indoor/dye-based inks. |
| Outdoor Suitability | This material was not designed for outdoor applications. For outdoor applications, Océ outdoor media and inks are recommended |
| Processing Tips | Outside of roll is side to be printed. Print in a dust and dirt free environment (60-85°F, 30-70% RH). Check and clean cartridge prior to printing. Recommended ink laydown not to exceed 400%. Use process black as opposed to composite black for optimum results. Océ equipment color profiles are available from the Océ web site: http://www.oceusa.com/resourcecenter For HP 2x00 and 3x00 printers use "test media" to determine best setting for printing. Allow the image to dry thoroughly prior to laminating or application. |
| Application Tips | This information is presented as a general guide only and is not a performance guarantee. Test first! This product will provide acceptable print image quality and dry times when used with the recommended OEM ink sets as noted in the Printer Compatibility chart on Océ website listed below. The user should independently determine, prior to use, the suitability of the material for the specific purpose. Recommended minimum surface application temperature for these products is 40°F. |
| User Tips | In order to prevent problems with cartridges, preventive maintenance by the customer on a daily basis is essential. Prior to starting your print job make a prime test plot. If not all nozzles are open, redo this test or make a "color test" print. Keep cartridges and their environment as clean as possible. Clean the service station assembly with water on a regular basis (preferably each day). Keep electrical contacts, flex cables and carrier clean from ink. Switch on the Auto Wipe mode. Be sure that the ink system is "closed"; there should be no air in the ink tubing system. Refill cartridges correctly (refer to the printer manual). Store cartridges correctly (use "print head garage"). |
| Color Profiles Display Graphics printers | For all Océ inks specific color profiles were developed to obtain maximum image quality. Color profiles are ink, media and machine specific. Profiles are available from website http://www.oceusa.com/resourcecenter |

Océ Imaging Supplies

Product Info

Photo Perfect Plus

Display Graphics

Version 2

9-23-04



Océ North America, Inc.

Océ Imaging Supplies

1800 Bruning Drive West

Itasca, IL 60143-1093

1-800-323-4827

www.oceusa.com

email: info@oceusa.com