

# CLEAR FOCUS ImageVue™ FILM

## Exterior Mount Product Specifications

Flexible Vinyl

Removable Adhesive

---

Black/White flexible 8-mil vinyl film with removable acrylic pressure-sensitive adhesive.

---

APPLICATIONS:	Windows, glass doors or other transparent surfaces
Makeup:	Black/White PVC with pressure-sensitive adhesive coating and release liner.
Open Area:	Approximately 35%
Vinyl Thickness:	.008" (.2mm)
Release Liner Thickness:	.007" (.17mm)
Adhesive Thickness:	.001" (.02mm)
Perforation Size:	.060" (1.5mm)
Dimensional Stability:	Good
Minimum Application Temperature:	40° F (4°C)
Service Temperature Range:	0°F to 140° F (-17°C to 60° C)
Expected Lifetime Exterior:	Two to three years. Six months for clean removal. Adhesion may increase with time.
Water Resistance:	Very good. If exposed to rain, printed image should be laminated.
Humidity Resistance:	Fair
Solvent Resistance:	Good
Storage Stability:	One-year shelf life when stored at 70°F (21° C) and 50% relative humidity.
Colors Available:	White print side and black adhesive side.
Printing:	Standard vinyl inks recommended. Print on the white side, not on the release liner.
Application:	Apply to clean, dry glass surface. Use plain soap and water, rinse and dry glass well. Do not use ammonia or other solvent-based glass cleaners prior to application. <b>Not for use on vehicle windows because of reduced visibility.</b>
Removal:	Remove by peeling from surface. Remove adhesive residue on older installations, if necessary.

CLEAR FOCUS Imaging, Inc., 60Maxwell Court, Santa Rosa, CA 95401, USA

Telephone (707) 544-7990 • Fax (707) 544-1886

E-mail: [headoffice@clearfocus.com](mailto:headoffice@clearfocus.com) • Website [www.clearfocus.com](http://www.clearfocus.com)