

Océ Outdoor Ultra-Durable Scrim Vinyl Banner - OBSCRM19

For outdoor signage and promotional banners

Product Description	An ultra-durable, no-tear, 19 mil heavy-weight high quality scrim vinyl. OBSCRM19 is coated with an ultra-durable, superior inkjet coating, producing sharp, long-lasting prints with pigmented inks.			
Physical Properties	Caliper	19 mil nominal		
	Opacity	100%min. (with a black out layer)		
	Whiteness	75 min.		
	Weight	17 oz. (583 g/m ²)		
	Tear strength	117 lb.		
	Tensile strength	229 lbs./in.		
	Gloss @ 60 degrees.	2.5		
Features	Pigment ink receptive. Scratch and tear resistance. Water resistance when using outdoor inks. Quick dry-time for overnight printing. Ideal for grommeting and sewing.			
Available sizes & Item Numbers	Width	x	Length	Item Numbers
	36"	x	40'	OBSCRM1901
	42"	x	40'	OBSCRM1902
	50"	x	40'	OBSCRM1903
	60"	x	40'	OBSCRM1904
	36"	x	5'	OBSCRM1905
Storage conditions and Shelf Life	Temperature 60-85°F. (15-30°C). Relative Humidity 40-60%. Please repack opened rolls when not in use. One year at conditions noted above. Allow material to adapt to room conditions 24 hours before printing.			
Environment, Health & Safety	No Material Safety Data Sheet required. Waste not suitable for recycling.			
Main applications	Designed for most demanding outdoor applications. Storefront displays. Trade shows and outdoor events Outdoor POP			
Lamination Tips	Suited for both hot and cold lamination. For heat activated lamination allow adequate dry time before lamination. Two-side lamination recommended as one side lamination may cause curl.			
Outdoor Suitability	This media is recommended mainly for outdoor applications. The information is given without guarantee and does not constitute a warranty. Outdoor life expectancy up to 12 months (unlaminated), only when OEM pigmented inks are used.			
Compatibility Chart	For printer compatibility tables and to find out what printers this product works best with, go to www.oceusa.com and download the latest version Océ compatibility chart.			

Océ-Imaging Supplies

Product Info

Outdoor Ultra-Durable Scrim Vinyl

Display Graphics

Version 1

6-11-03



Océ - Outdoor Ultra-Durable Scrim Vinyl Banner - OBSCRM19

For outdoor signage and promotional banners

Processing Tips	Outside of roll is side to be printed. Print in a dust and dirt free environment (59-85°F, 30-70%RH). Daily check and clean cartridge is recommended prior to printing. Recommended ink laydown not to exceed 300%. Use process black as opposed to composite black for optimum results. Océ equipment color profiles are available from the Océ web site: www.oceusa.com . For HP printers use "test media" to determine best setting for printing.
Application Tips	This information is presented as a general guide only and is not a performance guarantee. Test first! Product recommended for vertical application on flat surfaces.
User Tips	In order to prevent problems with cartridges, preventive maintenance by the customer on a daily basis is essential. Prior to starting your print job make a prime test plot. If all nozzles are not open, redo this test or make a "color test" print. Keep cartridges and their environment as clean as possible. Clean the service station assembly with water on a regular basis (preferably each day). Keep electrical contacts, flex cables and carrier clean from ink.
Color Profiles Display Graphics printers	For all Océ inks specific color profiles were developed to obtain maximum image quality. Color profiles are ink, media and machine specific. Profiles are available from web site http://www.oceusa.com/resourcecenter

Océ-Imaging Supplies

Product Info

Outdoor Ultra- Durable Scrim Vinyl

Display Graphics

Version 1

6-11-03

Performance on major Display Graphics Media

For performance of these inks on the various Océ Media please refer to the Product Information Sheets of the media.



Océ-USA, Inc. Océ-Imaging Supplies

1800 Bruning Drive West
Itasca, IL 60143-1093
1-800-323-4827
www.oceusa.com