

# CLEAR FOCUS **ClearLam**<sup>TM</sup>

## Polyester Overlaminates

### Physical Properties - Typical Performance Values Only

*Not for specification use*

<b>Backing</b>	<b>Super clear polyester</b>
<b>Adhesive</b>	<b>Water-based acrylic</b>
<b>Adhesion/Steel</b>	<b>14-17 oz./inch width</b>
<b>Elongation</b>	<b>125%</b>
<b>Tensile</b>	<b>26-28 lb./inch width</b>
<b>Film Thickness</b>	<b>.92 gauge (25 microns)</b>
<b>Overall Thickness</b>	<b>1.6 to 1.7 mil</b>
<b>Release Liner</b>	<b>Silicone / Polypropylene</b>
<b>Liner Thickness</b>	<b>1.5 mil (38 microns)</b>
<b>UV Resistance</b>	<b>Good to Excellent</b>
<b>FDA Approved</b>	<b>21 CFR 175.105</b>
	<b>21 CFR 177.10520</b>
<b>Outdoor Weathering</b>	<b>Fair to good</b>

CLEAR FOCUS Imaging, Inc. 60 Maxwell Court Santa Rosa, CA 95401 USA  
Tel.: (707) 544-7990 Fax: (707)544-1886 E-mail: [headoffice@clearfocus.com](mailto:headoffice@clearfocus.com) Web site:  
<http://www.clearfoc>