

LEXANTM SD14UV FILM

PRODUCT DATASHEET

DESCRIPTION

LEXANTM SD14UV Film is a one side fine velvet (FV), one side fine matte (FM) clear transparent laser markable polycarbonate overlay film that is typically used in government security documents, such as passport data pages, ID cards, driving licenses. Beside great printability and ease of processing (laminating, die-cutting, hot stamping), it offers the possibility to apply personalized security features into the card by use of UV laser marking. LEXANTM SD14UV Film is available in 50 and $100\mu m$.

TYPICAL PROPERTY VALUES◆

| PROPERTY | ASTM TEST METHOD | UNITS (USCS) | VALUE | ISO TEST METHOD | UNITS (SI) | VALUE |
|---|---------------------------------|---------------------------|----------------------|---------------------------------|---------------------------|----------|
| MECHANICAL | | | | | | |
| Tensile Strength @Yield | ASTM D882 | psi | 7830 | ISO 527 | MPa | 54 |
| @Break | ASTM D882 | psi | 9700 | ISO 527 | MPa | 67 |
| Tensile Modulus | ASTM D882 | psi | 300 x10 ³ | ISO 527 | MPa | 2080 |
| Tensile Elongation at Break | ASTM D882 | % | 137 | ISO 527 | % | 137 |
| THERMAL | | | | | | |
| Coefficient of Thermal Expansion, flow | ASTM E831 | (x 10 ⁻⁵ / °F) | 4.2 | ISO 11359 | (x 10 ⁻⁵ / °C) | 7.5 |
| Vicat Softening Temperature, B50 | ASTM 1525 | °F | 295 | ISO 306 | °C | 147 |
| Shrinkage at 130°C, 30min | Internal method | % | 0.17 | Internal method | % | 0.17 |
| PHYSICAL | | | | | | |
| Density | ASTM D792 | slug/ft3 | 2.33 | ISO 1183 | g/cm3 | 1.20 |
| Water Absorption, 24 hrs. | ASTM D570 | % change | 0.09 | ISO 62 | % change | 0.09 |
| Surface Roughness Ra | | μin | 23[FM] | ISO4288 | μm | 0.6 [FM] |
| | | | 102[FV] | | | 2.6[FV] |
| Surface Tension | Dyne solutions | Dyne/cm | 44 [FM] | Dyne solutions | Dyne/cm | 44 [FM] |
| | | | 38 [FV] | | | 38 [FV] |
| OPTICAL | | | | | | |
| Light Transmission | ASTM D1003 | % | 84 | ASTM D1003 | % | 84 |
| Color: b-value | CIELab, Reflection, D65, 10° | | 3.26 | CIELab, Reflection, D65, 10° | | 3.26 |

These are typical properties and are not intended for specification purposes. If minimum certifiable properties are required, please contact your local SABIC, Specialty Film & Sheet representative or the Quality Services Department. Reported Values are based on 0.100 mm (0.004") thickness film, except for the Coefficient of thermal expansion, Vicat softening temperature, Heat deflection temperature and water absorption, which are based on molded parts.

[™] Trademark of SABIC.

MANUFACTURING SPECIFICATIONS

NOMINAL GAUGE RANGES

MIN./MAX LIMIT OF NOMINAL

0.050 and 0.100 mm

±5%

CONTACT US:

SABIC CORPORATE HQ

PO Box 5101 Riyadh 11422 Saudi Arabia T +966 (0) 1 225 8000 F +966 (0) 1 225 9000 E info@sabic.com

AMERICAS

SABIC Functional Forms 2500 CityWest Boulevard Suite 100 Houston, TX 77042

USA

Toll-free (800) 323 3783 F (888) 443 2033

E spinside.sales@sabic.com

FUROPE

SABIC Functional Forms Plasticslaan 1 4612 PX Bergen op Zoom The Netherlands T +31 (0)164 293684 F +31 (0)164 292272

Eff.info@sabic.com

PACIFIC SABIC

Functional Forms 2550 Xiupu Road Pudong 201319 Shanghai

China

T +86 21 3222 4500 F +86 21 6289 8998 Eff.info@sabic.com

DISCLAIMER: THE MATERIALS, PRODUCTS AND SERVICES OF SAUDI BASIC INDUSTRIES CORPORATION (SABIC) OR ITS SUBSIDIARIES OR AFFILIATES ("SELLER") ARE SOLD SUBJECT TO SELLER'S STANDARD CONDITIONS OF SALE, WHICH ARE AVAILABLE UPON REQUEST. INFORMATION AND RECOMMENDATIONS CONTAINED IN THIS DOCUMENT ARE GIVEN IN GOOD FAITH. HOWEVER, SELLER MAKES NO EXPRESS OR IMPLIED REPRESENTATION, WARRANTY OR GUARANTEE (I) THAT ANY RESULTS DESCRIBED IN THIS DOCUMENT WILL BE OBTAINED UNDER ENDOLUTS, OR (II) AS TO THE EFFECTIVENESS OR SAFETY OF ANY DESIGN OR APPLICATION INCORPORATING SELLER'S RPODUCTS, SERVICES OR RECOMMENDATIONS. UNLESS OTHERWISE PROVIDED IN SELLER'S STANDARD CONDITIONS OF SALE, SELLER SHALL NOT BE RESPONSIBLE FOR ANY LOSS RESULTING FROM ANY USE OF ITS MATERIALS, PRODUCTS, SERVICES OR RECOMMENDATIONS DESCREBED IN THIS DOCUMENT. Each user is responsible for making its own determination as to the suitability of Seller's materials, products, services or recommendations for the user's particular use through appropriate end-use and other testing and analysis. Nothing in any document or oral statement shall be deemed to alter or waive any provision of Seller's Standard Conditions of Sale or this Disclaimer, unless it is specifically agreed to in a writing signed by Seller. Statements by Seller concerning a possible use of any material, product, service or design do not, are not intended to, and should not be construed to grant any license under any patent or other intellectual property right of Seller or as a recommendation for the use of any material, product, service or design in a manner that infringes any patent or other intellectual property right.

SABIC and brands marked with ™ are trademarks of SABIC or affiliates. © Copyright 2021 All rights reserved.

 $^\dagger Any$ brands, products or services of other companies referenced in this document are the trademarks, service marks and/or trade names of their respective holders.

